

Docket No. 1374.43736X00  
Serial No. 10/849,196  
August 30, 2006

**AMENDMENTS TO THE CLAIMS:**

The following listing of claims replaces all prior listings, and all prior versions, of claims in the application.

**LISTING OF CLAIMS:**

1-8. (Canceled).

9-19. (Canceled).

20. (Currently Amended) A semiconductor device comprising:

a semiconductor chip having over a main surface thereof an integrated circuit and plural electrodes;

plural leads arranged around said semiconductor chip;

plural wires ~~for electrically~~ connecting the plural electrodes on said semiconductor chip with the plural leads; and

a resin sealing member ~~for sealing~~ adapted to seal said semiconductor chip, portions of said plural leads and said plural wires;

wherein the plural leads ~~having~~ have plural first leads ~~includes~~ including first terminal portions respectively and plural second leads ~~includes~~ including second terminal portions respectively, the plural second leads each being disposed between adjacent ones of said first leads;

wherein end portions on one side of each of the plural first leads are positioned outside said semiconductor chip;

wherein end portions on one side of each of the plural second leads are fixed to a back surface of said semiconductor chip;

wherein the first terminal portions are arranged along side faces of the resin sealing member respectively; and

Docket No. 1374.43736X00  
Serial No. 10/849,196  
August 30, 2006

wherein the second terminal portions are arranged inside said first terminal portions respectively.

21. (Previously Presented) The semiconductor device according to claim 20, wherein said semiconductor chip is fixed to the end portions on one side of each of the plural second leads through a base which has a main surface and a back side.

22. (Previously Presented) The semiconductor device according to claim 21, wherein the end portions on one side of each of the plural second leads are fixed to the back side of the base.

23. (Canceled).

24. (Previously Presented) The semiconductor device according to claim 20, wherein the plural leads each have a first portion, a second portion bent from the first portion to a back surface of the resin sealing member, and a third portion extending from the second portion toward the side face of the resin sealing member.

25. (Previously Presented) The semiconductor device according to claim 24, wherein said semiconductor chip is fixed to the first portion; and

wherein the first terminal portions and the second terminal portions are formed in the third portion.

Docket No. 1374.43736X00  
Serial No. 10/849,196  
August 30, 2006

26. (Previously Presented) The semiconductor device according to claim 20,  
wherein the plural leads are fixed to said semiconductor chip through an adhesive.